

Brewer

Access[®] High-Low Exam Tables

Specifications

Brewer Differentiators

- *Industry-leading 700-lb. (317 kg) weight capacity for Model 6800/6801*
- *Combination of 18" (45.7 cm) low height in seated position and safety grab bars that rotate nearly 180° enables more confident transfers*
- *Exclusive SafeGlide™ leg extension allows caregivers to slide the heavy-duty extension in and out with minimal effort*
- *Innovative pass-through drawers and work surface offer access from either side*
- *Made in USA*

Product Specifications

- Weight capacity: 700 lbs. (317 kg) for Model 6800/6801, 450 lbs. (204 kg) for Model 6000/6001/6500/6501
- Seat Height: 18"-39" (45.7cm-99.06 cm)
- Length: 57"; extendable to 78" (144.8 cm-198.1 cm)
- SafeGlide™ leg extension length: 21" (53.3 cm)
- Lies flat at 28" (71.1 cm)
- Upholstery width: 28" (71.1 cm)
- Front storage drawer: 19.7" x 19.2" x 4" (50.3 cm x 48.8 cm x 9.7 cm)
- Side storage drawer: 22.6" x 20.2" x 7" (57.5cm x 51.4cm x 17.8cm)
- Paper storage capacity: 23"x 23"x 3.25" (58 cm x 58 cm x 8 cm)
- Slide through paper holder accepts 21" & 18" rolls (53.3 cm & 45.7 cm)



Model 6801 in Slate Blue

Standard Features

- Industry-best 3-year warranty
- Patient assist grab bars
- Adjustable stirrups
- Laptop work surface
- Easy on/off for patients
- Easy-to-clean, seamless upholstery
- Return-to-chair feature on power back models
- Adjustable backrest for easy patient positioning (pneumatic or power back available)
- Sensors to minimize possibility of injuries during table movement
- Anti-tamper on/off switch prevents accidental movement
- Foot control
- Low voltage actuators
- Single power cord design

The Power to Advance. Safely. Financially. Competitively.
www.brewercompany.com | P: 1.888.273.9371

Access[®] High-Low Exam Tables

Specifications

Optional Features

- Outlet for Model 6001:
 - 115VAC, 60 Hz, plant install only, must be ordered with table, orientation is on patient's left
- CAL-133 fire-resistant upholstery available in 4 colors
- Premium, plush upholstery available in 5 colors
- Custom colors available

Certifications

- UL 60601-1 compliant

Additional Specifications for Models 6801 and 6501

- Hospital-grade outlet – standard
- 115VAC, 60Hz
- 5° pelvic tilt
- 60 Watt front drawer heater

Models

- 6800 – Access High-Low 700 with power back
- 6801 – Access High-Low 700 with power back, pelvic tilt, front drawer heater and outlet
- 6500 – Access High-Low with power back
- 6501 – Access High-Low with power back, pelvic tilt, front drawer heater and outlet
- 6000 – Access High-Low with pneumatic back
- 6001 – Access High-Low with pneumatic back, pelvic tilt, and front drawer heater



Model 6801 in Black Satin

Model 6501 in Cocoa

Optional Accessories

- 99505 – Stainless Steel Treatment Pan
- 99502 – One Universal Socket Clamp
- 99504 – Deluxe Articulating Knee Crutches*
- 100253 – Urology Drain Pan System
- 100407 – Front Drawer Dividers
- 100540 – Two Support Adapters for Knee Crutches (factory installed)
- 100550 – Two Support Adapters for Knee Crutches (field installed)
- 101800 Electrical Outlet (6001 only - plant install - must order w/table)
- 102031 – Brewer Welch Allyn[®] IV Bracket (factory installed)
- 102032 – Brewer Welch Allyn[®] IV Bracket (field installed)

* Needs two 99502 and one of either 100540 or 100550

The Power to Advance. Safely. Financially. Competitively.

www.brewercompany.com | P: 1.888.273.9371

The Brewer Company is an ISO 13485:2003 certified company.

LIT-M-010-Rev A